# G-DRIV

## **SPECIFICATIONS**

Certification			Tier 3
No. of cylinders			6L
Injection System			ECR
Air Intake			TAA
Displacement	liters		8.7
Exhaust System			I-EGR
Stand-by Power @ 1500 rpm		kWm	256
Prime Power @ 1500 rpm		kWm	232
Stand-by Power @ 1800 rpm		kWm	280
Prime Power @ 1800 rpm		kWm	254
Code			CURSOR87TE3

## **WEIGHT AND DIMENSIONS**

Dimensions (L x W x H)	mm	2050 x 1055 x 1380
Dry Weight	Kg	1050

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

# Do you want to know more?

### LEGEND

Arrangement L (in line)

V (90° "V" configuration)

Air Handling

TC (Turbocharged)

NA (Naturally Aspirated)

TCA (Turbocharged with aftercooler)

Injection System

M (Mechanical)

ECR (Electronic Common Rail)

EUI (Electronic Unit Injector)

MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE



